

PRODUCT DATA SHEET



Surface Mounted Traffic Flow Control Plates



Traffic flow plates are normally specified to regulate traffic flow through one way systems within car parks, goods loading yards, bus lanes and similar applications.

They are simple to install, require no power, and easily enforce one way traffic patterns.

Rubber buffers are fitted to the reverse of surface mounted units, to ensure quiet operation.

Dimensions:

Surface Mounted (Non HGV): 305mm wide by 250mm depth by 100mm height.

Surface Mounted (HGV rated): 370mm wide by 250mm depth by 100mm height.

Installation Recommendations:

Traffic speed must be regulated to 5mph on the approach to the plates (speed ramps and warning signs are recommended)..

Provide a good level of illumination in the vicinity of the plates.

Lubricate the springs and hinges regularly.

Ensure that vehicles approach at an angle of less than 15 degrees.

Suggested Quantities to Suit Varying Road Widths.	
Road Width	Quantity of Plates
2.3m	5
2.5m	5
3.0m	6
3.5m	7
4.0m	8
4.4m	9
4.8m	10
5.3m	11
5.8m	12
6.2m	13

Recommended spacing is 300mm apart in both directions.



Physical Security Specialists
www.amcsecurity.com

Tel: +44 (0) 1273 463344
Fax: +44 (0) 1273 463544
Email: sales@amcsecurity.com